



HIGHEST PERFORMANCE FOR BUSINESS, LOGISTICS AND PRODUCTION

A3 Laser Printer for Just-in-Time Applications

HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- Minimal downtime and extremely long maintenance intervals
- ➤ Toner refill possible during operation
- Extremely fast printing speed
- Flexible expansion options for paper feed and tray
- Duplex printing at full printing speed
- Optional IPDS emulation making it the printer of choice for IBM® solutions

FIELD OF APPLICATION

- Just-in-time applications
- On-demand printing
- Business and workflow documents



Print Engine

Print technology Laser, OPC heat / pressure

Controller MPC 3.6

Print speed up to 105pages/minute (A4)

up to 52 pages/minute (A3)

Print resolution max. 600 dpi x 600 dpi

up to 400.000 pages (A4 landscape) **Duty cycle** (based on a using period of 60 months)

max. 500.000 pages (A4 landscape))

Power supply 220-240 VAC, 50 Hz

Power consumption 13A

Dimensions (WxDxH in mm) 870 x 760 x 980 (printer only)

1080 x 810 x 1190 mm (incl. Display)

ca. 300 kg (without options)

10 - 30°C **Environment temperature**

Relative humidity 20 - 85 % (rel., non condensing)

Interfaces USB

IEEE 1284 (Centronics) Ethernet-Interface

10/100/1000 MBit, bi-directional (TCP/IP)

Memory RAM: 2GB

Flash: 50MB



Emulations

MICROPLEX IDOL, HP-PCL5/ HPGL, AGFA Reno, µ-Postscript, LN03+, BULL-MP6090, Etimark MP-1220, TEC Bx72, TEC B6xx, Diablo 630, IBM Proprinter, EPSON FX-80 (ESC/P), MT-600/MT40, IDS, ANSI Genicom, TIFF, XML (SAP® RFID), CUPS Raster

Optional Emulations

CODE-V (Magnum), XEROX XES, KODESCRIPT+, Prescribe/PSB 2, IGP/PGL, Datamax, Labelpoint, LDC, ZPLII, EPL 2, Intermec Direct Protocol, IER Command, cab, Godex EZPL, HP Designjet, IPDS, AEA, PDF Direct Printing* (more emulations on request)

Barcodes

Codebar, Code39, MSI, PDF417, Interleaved 2/5, Interleaved 2/5 (3-Stroke Datalogic), Interleaved 2/5 (3-Stroke Matrix), EAN-8, 13, 128, Add-On-Codes, Code11, Code93, Code 128, UPC-A, UPC-E

Optional Barcodes (Barcode 2)

Datamatrix, Maxi-Code, QR Code, Aztec-Code, USD-5 (more barcodes on request)

Additional functions

Intelligent barcode generation on-the-fly in the printer

Format splitting in several subformats by command

Integrated form management (RFM) Forms and fonts can be stored in the flash memory

and can be accessed when needed

Optional functions

Status-out

gives notice of each correctly printed page via interface. Further features can be found in the manual.

Programmable GPIO-Interface (SPS-Control)

EMBEDDED INTELLIGENCE - Enabling two-way communication between printer and a PLC. Integration of the printer into production lines is possible, controlled by GPIO-interface Customer / Application specific modifications possible.

SPECIFICATIONS



Printable Media

A5R* - A3W* Size

Weight 60 to 220 g/m² max. 300 g/m

(option 3430 is required)



Paper Path

1+2: 1.200 and 800 sheets (A4/Letter) cassette 3: 500 sheets (B5R* bis A3W**) cassette 4: 500 sheets (A5R* to A3W**)

Optional

up tp 3.500 sheets A4, B5 (3433) up to 5.000 sheets (3430) (each 2.500 sheets in tray 5 and 6) A3W** - A5R* (no offset)

Output

faceup / face down

Optional

finisher saddle stitching (Art. 3440) 4000 sheets, 100-sheets-stitching A3 - B5R* (offset/stitching), A3W** - A5R (no offset) (more options on request)

* R = short side feeding **A3W = 12" x 18" (304mm x 457mm)

The brand names referred to are the registered trademarks of the respective companies. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 31.07.2023

MICROPLEX PRINTWARE AG Panzerstraße 5. 26316 Varel

Germany Phone: +49 4451 91370

E-Mail: sales@microplex.de

MICROPLEX PRINTWARE CORPORATION

30300 Solon Industrial Pkwy Suite E, Solon, OH 44139 IISΔ

Phone: +1 440-374-2424 E-Mail: info@microplex-usa.com



^{*} Only available from MPC 3.4, MPC 3.6, MPC 7.x and MPC 8.x