



Efficient Flash Fusing Printer for Sensitive Materials

HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- Prints on paper, PVC, plastic, etc.
- USB, Ethernet (10/100/1000 Mbit) as standard
- ▶ Laser and matrix printer compatible
- SAP® and AS/400 compatible (through PCL5 + JetCAPS as well as LAN-IPDS)
- Perfect control via Status Out

FIELD OF APPLICATION

- Label batch printing
- > Ticket printing
- Business and logistics documents



Print Engine

Print speed

Print technology

Controller

LED, OPC, xenon flash lamp

MPC 3.4 with Intel CPU

(>2 GHz CISC Processor)

3.000 lpm (6 lpi), up to 60 pages/minute (A4 landscape)

12,7 m/min

Print resolutionmax. 600 dpi x 600 dpiDuty cycleup to 300.000 pages

(based on a using period of 60 month)

 Power supply
 230V +/-10% / 50 Hz

 Power consumption
 max 4,5 kVA

(delivery with 32 Amp. connector)

 Acoustic noise
 < 55 dB (A)</td>

 Dimensions (WxDxH in mm)
 805 x 850 x 1250

 Weight
 240 kg (incl. Stacker)

Environment temperature 10 - 30°C

Relative humidity 30 - 80 % (rel., non-condensing)

Interfaces USB

Ethernet-Interface, 10/100/1000 MBit, bi-directional (TCP/IP)

Optional IEEE 1284 (Centronics),

WIFI IEEE 802.11 n/g/b,

WEP mit 64 und 128 Bit, WPA/WPA2, WPA-PSK/WPA2-PSK

Memory RAM: 4 GB Flash: 16 GB

MPC 3.3 High-End Print-Controller

Emulations

MICROPLEX IDOL, HP-PCL5/ HPGL, AGFA Reno, μ -Postscript, LN03+, BULL-MP6090, Etimark MP-1220, TEC Bx72, TEC B6xx, Diablo 630, IBM Proprinter, EPSON FX-80 (ESC/P), MT-600/MT40, IDS, ANSI Genicom, TIFF, XML (SAP® RFID), CUPS Raster

Optional Emulations

CODE-V (Magnum), XEROX XES, KODESCRIPT+, Prescribe/PSB 2, IGP/PGL, Datamax, Labelpoint, LDC, ZPLII, EPL 2, Intermec Direct Protocol, IER Command, cab, Godex EZPL, HP Designjet, IPDS, AEA, PDF Direct Printing*, (more emulations on request)

Barcodes

Codebar, Code39, MSI, PDF417, Interleaved 2/5, Interleaved 2/5 (3-Stroke Datalogic), Interleaved 2/5 (3-Stroke Matrix), EAN-8, 13, 128, Add-On-Codes, Code11, Code93, Code 128, UPC-A, UPC-E

Optional Barcodes (Barcode 2)

Datamatrix, Maxi-Code, QR Code, Aztec-Code, USD-5 (more barcodes on request)

Additional functions

Network capabilities authentication standard IEEE 802.1X

Intelligent barcode generation on-the-fly in the printer

Format splitting in several subformats by command

Integrated form management Forms and fonts can be stored in the flash memory (RFM)

and can be accessed when needed

Optional functions

Status-Out

gives notice of each correctly printed page via interface. Further features can be found in the manual.

Programmable GPIO-Interface (SPS-Control)

EMBEDDED INTELLIGENCE – Enabling two-way communication between printer and a PLC. Integration of the printer into production lines is possible, controlled by GPIO-interface Customer / Application specific modifications possible.

* only available with MPC 3.4, MPC 3.6, MPC 7.1 and MPC 8.x $\,$

The brand names referred to are the registered trademarks of the respective companies. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 22.08.2022

EMEA

MICROPLEX PRINTWARE AG Panzerstraße 5. 26316 Varel

Panzerstraße 5, 26316 Varel Germany

Phone: +49 4451 91370 E-Mail: sales@microplex.de

MICROPLEX PRINTWARE CORPORATION

30300 Solon Industrial Pkwy Suite E, Solon, OH 44139

Phone: +1 440-374-2424 E-Mail: info@microplex-usa.com




SPECIFICATIONS

Printable Media

Size

Form length 7" - 24"
With stacker 8" - 14"
Form width 6,5" - 16"
Printable area 14,6"

Weight 60 - 204 g/m²



Paper Path

Input

push tractor

Output

stacker

capacity: 3.000 pages (at 64 g/m²)

