

SOLID 58E MICR

Ideal for:

- Security - relevant documents / cheque printing
- Documents with 2D barcodes
- Documents with up to 18 inch material width

HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- Printing of cheques with MICR toner
- Cutter and tractor cassettes included
- USB, Ethernet (10/100 Mbit) as standard
- Laser and matrix printer compatible
- SAP and AS/400 compatible
- Perfect control via Status Out and GPIO (optional)

**FLEXIBLE DEPLOYMENT,
IMPRESSIVE COST
EFFECTIVENESS**



SOLID 58E MICR

The powerful and economical SOLID 58E can be flexibly deployed: thanks to the versatile Microplex Controller, it replaces matrix and laser printers and can be integrated in existing system environments with minimal effort. It is equipped with two tractor cassettes, an integrated cutter and can simultaneously print two A4 pages (2-up) at up to 58 pages per minute. For highest security needs, such as for printing checks, the SOLID 58E is equipped with MICR (Magnetic Ink Character Recognition) toner.

Print Engine

Print technology	LED, OPC, heat/pressure fixing
Controller	MPC 5.x with Intel XScale PXA 255 (400 MHz RISC processor)
Print speed	up to 58 pages/minute (A4 2-up) 8,6 m/min
Print resolution	600 dpi x 600 dpi
Duty cycle	up to 300.000 pages (based on a using period of 60 months, 12 x 17 inch) max. up to 1.275.000 pages (12 x 17")
Power supply	220 V -10/+6%, 50-60 Hz
Power consumption	7,5 A
Acoustic noise	< 55 dB (A)
Dimensions (WxDxH in mm)	890 x 780 x 350 mm 1120 x 780 x 1160 incl optional Stacker
Weight	164 kg (112 kg without options)
Environment temperature	15 - 30 °C
Relative humidity	25 - 55 % (rel., non-condensing)
Interfaces	Serial: USB 1.1, RS232/RS422 Parallel: IEEE 1284 (Centronics) LAN: Ethernet-Interface 10/100 MBit, bi-directional (TCP/IP)
Memory	RAM: 128 MB Flash: 16 MB

MPC 5.3 High-End Print-Controller

Emulations

MICROPLEX IDOL, HP-PCL5/ HPGL, AGFA Reno, µ-Postscript, LN03+, BULL-MP6090, Etimark MP-1220, TEC Bx72, TEC B6xx, Diablo 630, IBM Proprinter EPSON FX-80, MT-600/MT40, IDS, ANSI Genicom, TIFF, XML (SAP RFID), CUPS Raster

Optional Emulations

CODE-V (Magnum), XEROX XES, KODESCRIPT+, Prescribe/PSB 2, IGP-10, Datamax (FGL), Datamax Labelpoint, LDC, ZPL II, EPL 2, UPI Fingerprint, IER Command, Godex EZPL, HP Designjet, IPDS, AEA, AFP, Status-Out

Barcodes

Codebar, Code39, MSI, PDF417, Interleaved 2/5, Interleaved 2/5 (3-Strich Datalogic), EAN-8, 13, 128, Interleaved 2/5 (3-Strich Matrix), Add-On-Codes, Code11, Code93, Code 128, UPC-A, UPC-E

Optional Barcodes

Datamatrix, Maxi-Code, QR Code, Aztec-Code, USD-5 (more barcodes on request)

Additional functions

Intelligent barcode generation	on-the-fly in the printer
Format splitting	in several subformats by command
Integrated form management	up to 12 MB flash for forms and fonts inside the printer
Optional functions	

Status-Out

gives notice of each correctly printed page via interface

Programmable GPIO-Interface (SPS-Control) -

EMBEDDED INTELLIGENCE – Enabling two-way communication between printer and a PLC.

Integration of the printer into production lines is possible, controlled by GPIO-interface.

Customer / Application specific modifications possible.



Printable Media

Size

Form length	76 - 610 mm (3" - 24")
With stacker	178 - 432 mm (7" - 17")
Form width	152 - 457 mm (6" - 18")
Printable area	432 mm (17")

Weight

64 - 155 g/m²

Paper Path

Input

2 independent, detachable tractor cassettes

Output

rear: cutter

Optional

3.000 sheet stacker

The brand names referred to are the registered trademarks of the respective companies. All figures and details in italics and highlighted in color are optional. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 03.09.2018



Microplex Printware AG
Panzerstraße 5 | 26316 Varel | Germany
phone +49 4451 91 37-0 | fax +49 4451 91 37-49

