

logiJET T6-2

Ideal for:

- Stickers, labels and tags up to A5 size
- RFID inlays (optional)
- Just-in-time printing or batch processing

HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- Easy handling
- 1D and 2D barcodes
- IDOL Windows driver included
- Ethernet (10/100 MBit)
- Thermal and matrix emulation
- Automatic switching to active interface & emulation in dependency of interface
- Optional PCL5e emulation to run directly from SAP

MAXIMUM FLEXIBILITY FOR SMOOTH PRODUCTION AND LOGISTICS PROCESSES



logiJET T6-2

The logiJET T6-2 is a robust 6-inch thermal printer, designed to cope with the toughest demands in production and logistics. It prints fast and efficiently on all common materials, either in high-grade thermal transfer quality or with economical and especially efficient direct thermal printing. The logiJET T6-2 features impressive 300dpi resolution enabling, for example, very small barcodes or graphics to be depicted in clear, razor sharp quality. The high performance of the flexible Microplex Controller ensures optimal printing speeds at all times. With optional RFID functionality, UHF RFID inlays can be simultaneously coded during printing.

Print Engine

Print technology	Thermal transfer/direct thermal harmonic (history-controlled flat head technology)
Controller	MPC 8.x
Print speed	up to 150 mm/s up to 6 inch/s
Print resolution	300 dpi x 300 dpi
Lifetime print head	Transfer: up to 50.000 m, Direct: up to 25.000 m
Power supply	100 - 240 VAC, 50/60 Hz
Power consumption	3,3 A
Dimensions (WxDxH in mm)	345 x 516 x 285
Weight	17 kg (without options)
Environment temperature	5 - 40°C
Relative humidity	20 - 85 % (rel., non-condensing)
Interfaces	USB 2.0 Ethernet-Interface 10/100 MBit, bi-directional (TCP/IP)
Optional	IEEE 1284 (Centronics) RS232, RS422 WiFi: IEEE 802.11 n/g/b, WEP avec 64 et 128 Bit, WPA/WPA2, WPA-PSK/WPA2-PSK
Memory	RAM: 256 MB Flash: 256 MB

MPC 8.x High-End Print-Controller

Emulations

MICROPLEX IDOL, AGFA Reno, LN03+, BULL-MP6090, IGP-10, IGP/PGL, Datamax, Etimark MP-1220, TEC Bx72, TEC B6xx, LDC, ZPL II, EPL2, UBI Fingerprint, IER Command, cab, Godex EZPL, Diablo 630, IBM Proprinter, Epson FX-80 (ESC/P), MT-600/MT40, IDS, ANSI Genicom, TIFF, HP Designjet, XML (SAP® RFID), CUPS Raster

Optional Emulations

HP-PCL5/ HPGL, μ -Postscript, CODE-V (Magnum), XEROX XES, KODESCRIPT+, Prescribe/PSB 2, Labelpoint, Barcode 2, IPDS, AEA, AFP, RFM, Status-Out, PDF (more emulations on request)

Barcodes

Codebar, Code39, MSI, PDF417, Interleaved 2/5, Interleaved 2/5 (3-Stroke Datalogic), Interleaved 2/5 (3-Stroke Matrix), EAN-8, 13, 128, Add-On-Codes, Code11, Code93, Code 128, UPC-A, UPC-E

Optional Barcodes

Datamatrix, Maxi-Code, QR Code, Aztec-Code, USD-5 (more barcodes on request)

Additional functions

Network capabilities	authentication standard IEEE 802.1x
Intelligent barcode generation	on-the-fly in the printer
Format splitting	in several subformats by command

Optional functions

Integrated form management

flash memory for forms and fonts inside the printer

Status-Out

gives notice of each correctly printed page via interface. Further features can be found in the manual.

Programmable GPIO-Interface (SPS-Control)

EMBEDDED INTELLIGENCE – Enabling two-way communication between printer and a PLC.

Integration of the printer into production lines is possible, controlled by GPIO-interface
Customer / Application specific modifications possible.



Printable Media

Size

Width	max. 178 mm (165 mm withCutter) printable width 168 mm
roll diameter	max. 203 mm,
core diameter	1,5 - 3 inch (38,1 - 76,2 mm)

Paper thickness

0,06 mm - 0,25 mm

Thermal transfer ribbon


roll diameter max. 76 mm

Core diameter 1 inch (25.4 mm)

Ribbon length max. 450 m

Coated side inside or outside

Ribbon width 60 - 174 mm



Paper Path

Input

Continuous	internal: from roll external: e.g. fanfold
------------	---

sensor for black mark and label gap
(reflection and transmissive)

Output

Single/Job	tear-off
------------	----------

Optional

Continuous	internal Peeler / Rewinder
Single	peel-off, Cutter
Job	cutter

Option RFID

Frequency Range	865.600-867.600 (ETSI EN 302 208)
------------------------	--------------------------------------

RF Power

programmable in 15 levels (1dB step) from 9dBm to 23dBm (from 8mW to 200mW) conducted

Standard Protocols EPC C1 G2 / ISO18000-6C

Features read/write/verify (void)

Registration of antenna position

automatic (depending on antenna design)

The brand names referred to are the registered trademarks of the respective companies. All figures and details in italics and highlighted in color are optional. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 06.03.2020



Microplex Printware AG
Panzerstraße 5 | 26316 Varel | Germany
phone +49 4451 91 37-0 | fax +49 4451 91 37-49

