



SOLID T4-2

**MAXIMUM FLEXIBILITY
FOR SMOOTH
PRODUCTION AND
LOGISTICS PROCESSES**

4-Inch Thermal Printer for the Toughest Continuous use

HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- Optionally available in 5-inch width
- USB, Ethernet (10/100 Mbit) as standard
- Laser printer compatible
- SAP® and AS/400 compatible (through PCL5 + JetCAPS as well as LAN-IPDS)
- Very high printing speed
- Robust metal case
- Ribbon Safe Modus
- Enabled for remote printer management software SOTI Connect

FIELD OF APPLICATION

- Stickers, labels and tags up to DIN A4
- Roughest production and logistics operations
- Fast just-in-time printing or batch processing
- Toughest continuous use



Print Engine

Print technology	Thermal transfer/direct thermal harmonic (history-controlled near-edge print head)
Controller	MPC 8.x
Print speed	up to 406 mm/s up to 16 inch/s
Print resolution	300 dpi x 300 dpi
Lifetime print head	Transfer: up to 50.000 m, Direct: up to 25.000m
Power supply	110/240VAC, 50/60Hz
Power consumption	3,2 A
Dimensions (WxDxH in mm)	320 x 490 x 305
Weight	20 kg (without options)
Environment temperature	5 - 35°C
Relative humidity	45 - 75 % (rel., non-condensing)
Interfaces	USB, IEEE 1284 Ethernet-Interface 10/100 MBit, bi-directional (TCP/IP)
Optional*	RS232, RS422 WiFi: IEEE 802.11 n/g/b, WEP with 64 and 128 Bit, WPA/WPA2, WPA-PSK/WPA2-PSK
Memory	RAM: 256 MB Flash: 256 MB

MPC 8.x High-End Print-Controller

Emulations

MICROPLEX IDOL, HP-PCL5/ HPGL, AGFA Reno, LN03+, BULL-MP6090, IGP/PGL, Datamax, Etimark MP-1220, TEC Bx72, TEC B6xx, LDC, ZPL II, EPL2, Intermec Direct Protocol, IER Command, cab, Godex EZPL, Diablo 630, IBM Proprinter, Epson FX-80 (ESC/P), MT-600/MT40, IDS, ANSI Genicom, TIFF, HP Designjet, XML (SAP® RFID), CUPS Raster, PDF Direct Printing**

Optional Emulations

µ-Postscript, CODE-V (Magnum), XEROX XES, KODESCRIPT+, Prescribe/PSB 2, Labelpoint, IPDS, AEA, (more emulations on request)

Barcodes

EAN 8, 13, 128, add on, 2/5 3-stroke Datalogic, 2/5 3-stroke Matrix, Codabar, PDF 417, Royalbar, Planet, Jetcaps (HP/SAP), Code 39, 128 MSI, UPC A, E, Postnet, KIX, USPS One Code

Optional Barcodes (Barcode 2)

Datamatrix, Maxi-Code, QR Code, Aztec-Code, USD-5 (more barcodes on request)

Additional functions

Network capabilities	authentication standard IEEE 802.1X
Intelligent barcode generation	on-the-fly in the printer.
Format splitting	in several subformats by command.
Ribbon Save Mode	active from 12 mm unprinted length, to save ribbon.
Remote Management Support	SOTI Connect (License necessary)

Optional functions

Integrated form management (RFM)

Forms and fonts can be stored in the flash memory and can be accessed when needed.

Status-Out

gives notice of each correctly printed page via interface. Further features can be found in the manual.

Programmable GPIO-Interface (SPS-Control)

EMBEDDED INTELLIGENCE – Enabling two-way communication between printer and a PLC.


Integration of the printer into production lines is possible, controlled by GPIO-interface.

Customer / Application specific modifications possible.



Printable Media

Size	25,4 - 154 mm width printable width 106 mm
5" width	25,4 - 154 mm width 128 mm printable
Roll diameter	max. 210 mm (max 4250 g)
Core diameter	1,5 / 3 / 4 Inch (38,1 - 102 mm)
Weight	max. 240 g/m ²
Paper thickness	0.2 - 0.9 mm
Thermal transfer ribbon	roll diameter max. 90 mm
Core diameter	1 inch (25.4 mm)
Ribbon length	max. 600 m
Coated side	inside (outside possible)
Ribbon width	30 - 110 mm
5" width	30 - 132 mm



Paper Path

Input

Continuous
internal from roll, external, e.g. fanfold
standard: Gap sensor (transmissive)
optional: Black Mark sensor (reflection)

Output

Single / Job tear-off

Optional

Continuous external rewinder
Single peel-off, Cutter
Job cutter

* Not all interface options can be activated at the same time.
** Only available with MPC 3.6, MPC 7.x and MPC 8.x

The brand names referred to are the registered trademarks of the respective companies. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 29.10.2025

EMEA
APAC

MICROPLEX PRINTWARE AG
Panzerstraße 5, 26316 Varel
Germany
Phone: +49 4451 91370
E-Mail: sales@microplex.de

AMER
Canada

MICROPLEX PRINTWARE CORPORATION
30300 Solon Industrial Pkwy Suite E, Solon, OH 44139
USA
Phone: +1 440-374-2424
E-Mail: info@microplex-usa.com

